

INTER-PAK SERIES SC-200 STATIONARY COMPACTOR



FEATURES & SPECS

CHARGE BOX

- **CYCLE TIME:** EXT: 40 SEC REC: 35 SEC
- **OPENING:** 41" L X 60" W
- **SIDES:** 3/16" THICK WITH STRUCTURAL SUPPORTS
- **FLOOR:** 3/8" THICK PLATE WITH 4" CHANNEL CROSSMEMBERS
- **BREAKER BAR:** 6" X 8" X 1"

RAM

- **FACE PLATE:** 3/8" THICK WITH 6" CHANNEL CROSSMEMBERS
- **BOTTOM:** 3/8" THICK
- **SIDES:** 1/4" THICK
- **TOP:** 7G THICK WITH 4" CHANNELS
- **GUIDES:** REPLACEABLE 3 POINT NYLATRON GUIDES
- **PENETRATION:** 15"
- **NORMAL FORCE:** 50,800 LBS
- **MAX FORCE:** 56,500 LBS
- **RAM FACE PRESSURE:** NORMAL: 29.9PSI, MAX: 33.2 PSI

ELECTRICAL

- **MOTOR:** 10HP/3-PHASE 208/230/460 VAC
- **CONTROL VOLTAGE:** 120 VAC
- 15' REMOTE PENDANT WITH 4 BUTTON STATION
- 15' REMOTE COLOR-CODED PRESSURE GAUGE
- KEY AUTO/HAND, EMERGENCY STOP WITH LIGHT, START, FOR/REV
- 100% LIGHT

HYDRAULIC

- **RESERVOIR CAPACITY:** 28 GALLONS
- **PUMP:** 10.5 GPM
- **NORMAL PRESSURE:** 1800 PSI
- **MAX PRESSURE:** 2000 PSI
- **HYDRAULIC CYLINDER:** BORE: 6", ROD: 2.5", STROKE: 56"

INTER-PAK SERIES SC-200 STATIONARY COMPACTOR

AVAILABLE OPTIONS

- PREMIUM POWER UNIT
- 80% FULL LIGHT
- HEAVY DUTY CYLINDER
- OIL TANK HEATER
- DOOR COUNTER SYSTEM
- LOW TEMPERATURE OIL
- MONITORING SYSTEM
- PHOTO ELECTRIC EYE
- DOG HOUSES, ENCLOSURES
- WALK ON DECK, DRIVE ON DECK

COLORS

*COLOR MATCH AVAILABLE

 Extra White F75WC7	 International Red F75RC7	 Implement Orange F75EC9	 Implement Yellow F75YC18	 Equipment Yellow F75WC7	 Enviro Green F75GC19	 Equipment Blue F75LC14	 Ravens Black F75BC14
 Starburst White SW74C9	 Allen Red SW7417	 Machinery Red SW7422	 Power Orange SW7413	 Heavy Equip. Orange SW7412	 Agricultural Yellow SW7410	 Tractor Green SW7420	 Equipment Green SW7429
 Blue Ribbon SW7421	 Motor Blue SW7416	 Equipment Tan SW7411	 Primer EG1A400	 Jet Black Sher-Kem Low Gloss SW7424 F75TC1	 Jet Black Sher-Kem Semi Gloss SW7474 F75BC17	 Jet Black Sher-Kem Fast Dry SW7474 F75B203	

DIMENSIONS

