

APT-40X APARTMENT COMPACTOR

FEATURES & SPECS
CHARGE BOX

- **CYCLE TIME:** 14 SECONDS
- **OPENING:** 22.5" X 30"
- **SIDES:** 3/16" THICK WITH STRUCTURAL SUPPORTS
- **FLOOR:** 3/8" THICK PLATE WITH 3" CHANNEL CROSSMEMBERS
- **BREAKER BAR:** 4" X 4" X 1/2"

RAM

- **FACE PLATE:** 3/8" THICK
- **BOTTOM:** 3/8" THICK
- **SIDES:** 3/16" THICK
- **TOP:** 1/4" THICK WITH 4" CHANNELS
- **PENETRATION:** 4"
- **NORMAL FORCE:** 13,900 LBS | **MAX FORCE:** 16,400LBS
- **RAM FACE PRESSURE:** NORMAL: 23.16 PSI | MAX: 27.33PSI

ELECTRICAL

- **MOTOR:** 5 HP 3-PHASE 208/230/460 VAC
- **CONTROL VOLTAGE:** 120 VAC
- **15' REMOTE PENDANT WITH 4 BUTTON STATION**

- **15' REMOTE COLOR-CODED PRESSURE GAUGE**
- **KEY AUTO/HAND, EMERGENCY STOP WITH LIGHT, START, FOR/REV**
- **100% LIGHT:** 1650 PSI
- **PHOTO EYE/ LIGHT AND SIREN FOR AUTO START INCLUDED**

HYDRAULIC

- **RESERVOIR CAPACITY:** 13 GALLONS
- **PUMP:** 6 GPM
- **NORMAL PRESSURE:** 1650 PSI **MAX PRESSURE:** 1950 PSI
- **HYDRAULIC CYLINDER:** BORE: 2.5" | ROD: 1.25" | STROKE: 18.5"

AVAILABLE OPTIONS

- **OIL TANK HEATER**
- **LOW TEMPERATURE OIL**
- **80% FULL LIGHT**



APT-40X APARTMENT COMPACTOR

COLORS



***COLOR MATCH AVAILABLE**

PRODUCT MANUAL

Scan this QR code below to view/download the product's manual:



DIMENSIONS

